

**SENSIT<sup>®</sup> TKX**  
COMBUSTIBLE GAS LEAK DETECTOR

SENSIT

TICK ADJUST

SENSIT

**SENSIT<sup>®</sup> TKX**  
makes leak detection quick and easy!

MADE IN USA

**SENSIT**  
Technologies

Innovative Detection Solutions

[www.gasleaksensors.com](http://www.gasleaksensors.com)

# SENSIT<sup>®</sup> TKX

## COMBUSTIBLE GAS LEAK DETECTOR

**SENSIT<sup>®</sup> TKX** is the perfect choice when locating hard to find natural gas or propane gas leaks. Low maintenance and low initial cost make this product the ideal choice for the budget conscious.

### FINDS LEAKS QUICKLY

- High sensitivity allows immediate leak detection
- Tick rate control to pinpoint leaks fast
- Detects many gases and chemicals

### LOW MAINTENANCE

- Solid state sensor
- Alkaline battery powered
- Lowest cost of ownership

### TKX Standard Features

- Long battery life
- Long sensor life
- Adjustable tick rate system
- Audible and Visual Indicators
- SENSIT<sup>®</sup> quality and durability



### INDUSTRY USERS

Utility Operators  
Emergency Vehicles  
Fire Departments  
Appliance Repair  
Marine Operations  
Plant Maintenance  
Heating and A/C Contractors  
Plumbing Contractors  
Housing Maintenance

### APPLICATIONS

Gas Pipe Leak Detection  
Propane / Butane Bottle Checks  
Chemical Detection  
Arson / Accelerant Detection

### PARTIAL LIST OF GASES SENSED\*

Acetone	Hydrogen
Alcohol	Industrial Solvents
Ammonia	Jet Fuel
Butane	Lacquer Thinner
Ethylene Oxide	Methane
Gasoline	Natural Gas
Halon	Propane

\*Contact Sensit Technologies for more info.



SENSOR  
 ON / OFF SWITCH  
 SENSING INDICATOR  
 TICK ADJUST DIAL  
 FLEXIBLE GOOSENECK  
 BATTERY COMPARTMENT

- TO OPERATE:**
1. Power On
  2. Wait 30 Seconds
  3. Adjust Tick
  4. Begin to Use

Patented



**STANDARD KIT**

Carrying Pouch  
 3 "C" Batteries  
 Instruction Manual

**SENSOR SPECIFICATIONS**

TYPE	DETECTION LIMIT	RANGE
PPM	20ppm	20-50,000

**PRODUCT SPECIFICATIONS**

Size:	3.5" x 10" x 1.6" (8.9 x 25.4 x 4 cm)
Weight:	1.3 pounds (0.59 kg)
Operational Temp:	0 to 120° F (-20 to 50° C)
Battery Life:	Alkaline: Approximately 30 hrs. Continuous



SENSIT® TKX instruments are approved UL913,  
 For Class 1, Division 1, Groups C and D, T3  
 hazardous locations when used with Duracell  
 MN1400BK batteries or equivalent alkaline batteries.

## SENSIT® TKX Instruments

SENSIT TKX  
Part # 902-00000-02

Included with instrument:  
Instrument Pouch, 3 "C" Batteries, and Instruction Manual

## SENSIT® TKX Standard Kit Replacement Parts

Sensor EX (LEL) (2611 Silver 4 Prong)  
Part # 375-2611-01

Sensor Cap  
Part # 365-00045

Instrument Pouch  
Part # 360-00002

Instruction Manual  
Part # 750-00043



851 Transport Drive  
Valparaiso, IN 46383-8432

Phone: 888 4SENSIT  
888 473 6748  
219 465 2700

Fax: 219 465 2701  
[www.gasleaksensors.com](http://www.gasleaksensors.com)

**MADE IN USA**

SENSIT Technologies  
is in compliance with ISO 9001:2008



Distributed by:

