

# SENSIT® HXG-3 COMBUSTIBLE GAS LEAK DETECTOR

SENSIT® HXG-3 is an advanced state-of-the-art combustible gas leak detector capable of sensing many combustible gases such as methane, propane and natural gas.

The backlit LCD display shows percent lower explosive limit (LEL) and part-per million (ppm) readings simultaneously for accurate leak detection and analysis. Audible and visual alarms warn of potential hazardous conditions.

# **Pinpoint Leaks**

Leaks can easily be pinpointed by using an audible tick rate. The sensor is located at the end of a flexible gooseneck to easily reach areas where leaks may be suspected.

# **Data Save**

A Data Save feature allows you to save data during any investigation.

# **HXG-3 Standard Features**

- Displays LEL and PPM
- Infrared Downloading
- Long-life, Low-Cost Sensor
- Simple Calibration



# **INDUSTRY USERS**

Natural Gas Companies **Propane Suppliers** 

Electric Companies

Safety Engineers

Fire and Police

**Emergency Vehicles** 

Appliance Repair

Plant Maintenance

Plumbing Contractors

Marine Operations

Heating and Air Conditioning

**Municipalities** 

Mobile Home Parks

**Apartment Buildings** 



# **APPLICATIONS**

Confined Space Monitoring

Vessel Testing

Manhole Entry

Vault Entry

Leak Detection

Leak Pinpointing

Pipeline Purging



#### PARTIAL LIST OF GASES SENSED\*

Acetone

Industrial Solvents

Alcohol

Jet Fuel

Ammonia

Lacquer Thinner

Butane Ethylene Oxide Methane

Gasoline

Natural Gas

Halon

Propane Refrigerants

Hydrogen

<sup>\*</sup>Contact Sensit Technologies for more info.





Hard Carrying Case 3 "C" Batteries Wrist Strap Instruction Manual Optional PPM Probe Assembly Printer PC Interface Calibration Kit

#### **OPTIONAL FEATURES**

#### Internal Pump (HXG-3P):

Provides Faster Response Provides Better Sensor Protection



#### **SENSOR SPECIFICATIONS**

TYPE	RESOLUTION	RANGE	<b>ACCURACY</b>

PPM\* 1 or 10ppm 0-50,000 ppm N/A LEL 0.1% 0-100% LEL ±10%

\*PPM Optional

#### **PRODUCT SPECIFICATIONS**

Size: 11.5" x 3" x 2.2" (29.21 x 7.62 x 5.89 cm)

Weight: 1.2 lb. (0.54 kg)

Operational Temp: -20 to 120 F (-28.9 to 48.9° C)

Battery Life: Alkaline: Approximately 30 hrs. Continuous

**CE EX II 3 G**EEx ic IIB T3

ATEX File No. NA45026-01X

#### **SENSIT® HXG-3 Instrument (No Pump)**

SENSIT HXG-3 (No Pump) Part # 907-00000-02

# **SENSIT® HXG-3 Standard Kit Replacement Parts**

Sensor EX (LEL) (2611 Silver 4 Prong) Part # 375-2611-01

Sensor Cap Part # 365-00045

Hard Carrying Case Part # 872-00001

Wrist Strap Part # 360-00040

Instruction Manual Part # 750-00023

# SENSIT® HXG-3P Instrument (With Pump)

SENSIT HXG-3P (With Pump) Part # 907-00000-08

# SENSIT® HXG-3P Standard Kit Replacement Parts

Sensor EX (LEL) (2611 Silver 4 Prong) Part # 375-2611-01

Sensor Cap (Replacement) w/"O" Rings Part # 870-00018

Hard Carrying Case Part # 872-00001

Wrist Strap Part # 360-00040

Instruction Manual Part # 750-00027

# SENSIT® HXG-3 Manual Calibration Kits

Methane Calibration Kit (21 liter 2.5% Methane) Part # 881-00015

Pentane Calibration Kit (34 liter 50% Pentane) Part # 881-00077

# **SENSIT® HXG-3P Manual Calibration Kits**

Methane Calibration Kit (21 liter 2.5% Methane) Part # 881-00016

Pentane Calibration Kit (34 liter 50% Pentane) Part # 881-00067

# **SENSIT® HXG-3/3P Replacement Cylinders**

2.5% Methane/Air (21 Liter) Part # 315-080012

2.5% Methane/Air (221 Liter) Part # 315-180013

Pentane (50% LEL) (34 Liter) Part # 315-100003



**MADE IN USA** 

851 Transport Drive Valparaiso, IN 46383-8432

Phone: 888 4SENSIT 888 473 6748

219 465 2700

219 465 2701 Fax:

www.gasleaksensors.com

**SENSIT Technologies** is in compliance with ISO 9001:2008











